

ASSEMBLY AND INSTALLATION

INSTRUCTIONS FOR

ITEM #137SF/# 140SF

WARNING:

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Should any difficulty be experienced, please consult a qualified electrician before installing.

Installation steps:

1. Turn off the electricity at the Fuse or Circuit Breaker before installation.

2. Attach the Cross Bar to the Outlet Box by the 2pcs Mounting Screws upwards.

3. Attached the Central Tube to the Connector, then adjust the Central Tube to be vertical and fix it with the Small Screw.

4. Install Bulbs. (Bulbs are not included, please do not exceed the maximum capacity which is recommended on the Socket Cover.)

5. Attached the End Cap and Finial to the Nipple, and put the glass into the Metal Ring.

6. Attached the Small Chain to the Bottom Hanging Hook.

7. Make wire connection with Wire Connectors:

----Connect the black Wire from the light to the Black Wire from the Outlet Box.

----Connect the white Wire from the light to the White Wire from the Outlet Box.

----Attached the Ground Wire and House Ground Wire to the Cross Bar with a Green Screw.

Carefully tuck wires back into the Outlet Box.

8. Carefully raise up the fixture and insert the 2pcs of Short Mounting Screws into the Canopy and tighten with the Fixing Nuts.

9. Turn on the power at Fuse or Circuit Box and enjoy your new fixture.

