

# ASSEMBLY AND INSTALLATION INSTRUCTIONS

**WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.**

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

## Installation Steps:

1. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to lose any small parts necessary for installation.
2. Attach the mounting plate to the outlet box using two outlet box screws as shown. The side of the mounting plate marked "GND" must face out.
3. Guide the supply wires and ground wire from outlet box through the center hole on the mounting plate.
4. Make wire connections:
  - attach fixture ground wire to supply ground wire using a wire nut or attach them to the mounting plate with a green ground screw.
  - attach white wire from light to white wire from power source with a wire nut.
  - attach black wire from light to black wire from power source with a wire nut.Observing: ground wire with ground wire, neutral wire with neutral wire, hot wire with hot wire.  
\*\*\*Make sure all wire connectors are secured and do not easily pull off with the slight tug.
5. Once all wires are connected, tuck them carefully into outlet box.
6. Place the back plate over mounting plate and secure back plate to mounting plate with mounting screws.
7. Raise the socket ring into the socket wrench and spacer onto the socket wrench; attach the glass shade to the socket, lock it securely with the socket wrench, then remove the socket wrench and save it.
8. Install bulbs.(not included) (Please do not exceed the maximum capacity which is recommended on the fixture.)
9. Turn on the power at fuse or circuit box.

NOTE: To clean, wipe fixture with a damp soft cloth. Then dry immediately with a dry soft cloth. Clean glass with a mild soap. DO NOT use chemical cleaners or abrasive materials such as scouring pads or powders, steel wool or abrasive paper.

