

ASSEMBLY AND INSTALLATION INSTRUCTION

WARNING: SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER!

NOTE: BEFORE INSTALLING, CONSULT LOCAL ELECTRICAL CODES FOR WIRING AND GROUNDING REQUIREMENT.

Installation Steps:

1. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to lose any small parts necessary for installation.
2. Attach the mounting plate to outlet box by using two outlet box screws.
3. **See the Fig.1.** Attach the Glass into the Frame, fixed with the Iron shims.
4. **See the Fig.2.** Raise the Square plate, Arm set and Clips onto the top corner of frame, aim mounting holes, lock it securely with the Screws. Using the screw fixed center pipe.
5. **See the Fig.3.** Raise the assembled lamp body onto the outlet box, guide the supply wires and ground wire from outlet box through the center hole on the mounting plate.

Make wire connections:

--attach ground wire to house ground wire using a wire nut or attach them to the back plate with a green ground screw.

--attach white wire from light to white wire from power source with a wire nut.

--attach black wire from light to black wire from power source with a wire nut.

Observing: ground wire with ground wire, neutral wire with neutral wire, hot wire with hot wire.

***Make sure all wire connectors are secured and do not easily pull off with the slight tug.

5. Once all wires are connected, tuck them carefully into outlet box.
6. Place the back plate over Mounting screws, lock it securely with the Ball nuts. Raise the candle sleeve to the lamp holder.
7. Install bulbs.(not included) (Please do not exceed the maximum capacity which is recommended on the fixture.)
8. Turn on the power at fuse or circuit box.

NOTE: To clean, wipe fixture with a damp soft cloth. Then dry immediately with a dry soft cloth. Clean glass with a mild soap. DO NOT use chemical cleaners or abrasive materials such as scouring pads or powders, steel wool or abrasive paper.

