

# INSTALLATION INSTRUCTIONS

## Model 5018PHXKR-BK

**FOR YOUR SAFETY WARNING: BE SURE THE ELECTRICITY TO THE WIRES YOU ARE WORKING ON IS SHUT OFF; EITHER THE FUSE IS REMOVED OR THE CIRCUIT BREAKER IS SHUT OFF. GENERAL** You don't need special tools to install this fixture. Be sure to follow the steps in the order given. Under no circumstances should a fixture be hung on house electrical wires, nor should a swag type fixture be installed on a ceiling which contains a radiant type heating system. Read instructions carefully. If you are unclear as to how to proceed, consult a qualified electrician.

**NOTE: Proper wiring is essential for the safe operation of this fixture.**

### HANGING THE FIXTURE (Fig. 1)



1. Shut off the power at the circuit breaker and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Take off the cage (I) from the bottom plate (E) by loosening mounting screws (D)
4. Lower the post (A) toward pole, hang post (A) on the pole by safety cable w/hook(B) ( This will allow for the fixture to be supported while wire connections are made.)

### CONNECTINE THE WIRES (Fig.2)

5. While supporting the fixture, connect the electrical wires as shown in figure 2. If your post has a ground wire (green or bare copper), connect the fixture ground wire to it. If not, consult your electrician for proper grounding. After the wires are connected, tuck them carefully inside the post (A).
6. Place the fixture onto pole, and secure with the 4 mounting screws (C)

### COMPLETING THE INSTALLATION (Fig. 1)

7. Insert caps (G) on the candle covers (F).
8. Install the bulb (E12 Candelabra base, not included.) in accordance with the fixture's specification.
9. Attach the cage (I) back to the bottom plate (E) by mounting screws (D).



## ASSEMBLY AND INSTALLATION INSTRUCTIONS

**WARNING:** Be sure the electricity to the wires you are working on is shut off, either the fuse is removed or the circuit breaker is shut off.

**NOTE:** Before installing, consult local electrical codes for wiring and grounding requirements.

Carefully remove the fixture from the carton, and check that all parts are included, as shown in figure. Be careful not to misplace any of the screws or parts which are needed for installing the fixture.

### Assembly and Installation Step:

1. Drill 4 holes 35mm deep for the Anchor sleeves and insert Wood screws so they are flush with the surface.
2. Place the Post of Fixture to the Base, and then secure with 3 Mounting Screws.

